

PF7217ESSLights Specification Sheet



The PF7217ESSLights Automatic Rising Bollard

Luxury Heavy Duty Electro Mechanical Bollard in Stainless Steel - 210mm Diameter/700mm Above ground. Comes complete with flashing lights around rim and on top.

Voltage 230 V +/- 10% 50-60Hz
Power Absorbed 400W
Power & Speed 0.18 kW,
(0.25HP); 2,800RPM
Duty Cycle 1,500 Cycles Per
Day / 60 Cycles per Hour
Working Temperature -15°C to
+60°C
Mechanics Reversible; rolled
worm screw
Operation Time Approx. 7
Seconds including slowing down
Emergency Release Lowers
automatically with power cut off
Maximum Thrust Force 1000 N
max. during rod raising phase
Size (Buried Casing) 273mm
Diameter X 915mm
Size (Bollard) 210mm Diameter
X 700mm High
Finish Stainless Steel
Bollard Material Stainless Steel
Lights 4 No. On Top High
Intensity L.E.D.s & 8 No. Radial
L.E.D.s
Protection Level IP67
Cable Length 10m
Weight 100Kg
Reflective Film 50mm Silver

Reflexite
DYNAMIC LOAD (impact Height
300mm)
Crash Resistance 8,000 J
Break in Resistance 400,000 J
AXIAL LOAD
Raised Bollard Max 5,000 N
Lowered Bollard Max 150,000 N
OPTIONS
500mm or 700mm High
Stainless Steel or Powder
Coated Finish
With or Without Lights
Fail 'Safe' or Fail 'Secure'
Siren Detector for Automatic
Lowering for Emergency
Services
Anti-Tamper Alarm
Road Loops and Photo Cells
Traffic Lights
Numerous Access Control
Systems including Push
Buttons, Radion Receivers,
Keypads, Card Readers,
Intercoms & Transponders



EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SHEET HOWEVER WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.